

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : C+P Der Reiniger für Stahlschränke  
Revision date : 10.02.2023  
Print date : 11.05.2023

Version (Revision) : 2.0.6 (2.0.5)

**SECTION 1: Identification of the substance/mixture and of the company/ undertaking**

**1.1 Product identifier**

C+P Der Reiniger für Stahlschränke

**1.2 Relevant identified uses of the substance or mixture and uses advised against**  
**Relevant identified uses**

PC 35 - Washing and cleaning products

**1.3 Details of the supplier of the safety data sheet**

**Supplier**

C + P Möbelsysteme GmbH & Co. KG

**Street :** Boxbachstr. 1

**Postal code/City :** 35236 Breidenbach

**Telephone :** 06465 919 0

**Telefax :** 06465 919 200

**Information contact :** einkauf.breidenbach@cp.de

**1.4 Emergency telephone number**

06465 919 0 during normal office hours  
(Monday to Thursday from 8 am to 5 pm and Friday from 8 am to 3 pm)

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

None

**2.2 Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Special rules for supplemental label elements for certain mixtures**

EUH210 Safety data sheet available on request.

**2.3 Other hazards**

None

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Hazardous ingredients**

ETHANOL ; REACH No. : 01-2119457610-43-XXXX ; EC No. : 200-578-6; CAS No. : 64-17-5

Weight fraction :  $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319

Specific Conc. Limits : Eye Irrit. 2 ; H319: C  $\geq 50 \%$

2-BUTOXYETHANOL ; REACH No. : 01-2119475108-36-XXXX ; EC No. : 203-905-0; CAS No. : 111-76-2

Weight fraction :  $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Acute Tox. 3 ; H331 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319  
Substance with a common (EC) occupational exposure limit value.

Specific Conc. Limits : (ATE - oral : 1200 mg/kg) • (ATE - inhalative (vapour) : 3 mg/L)

**Additional information**

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

**SECTION 4: First aid measures**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : C+P Der Reiniger für Stahlschränke  
Revision date : 10.02.2023  
Print date : 11.05.2023

Version (Revision) : 2.0.6 (2.0.5)

#### 4.1 Description of first aid measures

##### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

##### Following inhalation

Remove casualty to fresh air and keep warm and at rest.

##### In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

##### After eye contact

Protect uninjured eye. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

##### Following ingestion

Rinse mouth thoroughly with water. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

None

#### 4.3 Indication of any immediate medical attention and special treatment needed

None

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Water Foam Extinguishing powder Carbon dioxide (CO<sub>2</sub>) Sand Nitrogen Extinguishing blanket

##### Unsuitable extinguishing media

Full water jet

#### 5.2 Special hazards arising from the substance or mixture

##### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide , Carbon dioxide (CO<sub>2</sub>) , Nitrogen oxides (NO<sub>x</sub>).

#### 5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### 5.4 Additional information

Move undamaged containers from immediate hazard area if it can be done safely. Co-ordinate fire-fighting measures to the fire surroundings.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product.

#### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

#### 6.3 Methods and material for containment and cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Wash with plenty of water. Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : C+P Der Reiniger für Stahlschränke  
Revision date : 10.02.2023  
Print date : 11.05.2023

Version (Revision) : 2.0.6 (2.0.5)

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Keep container tightly closed. Avoid: Inhalation of vapours or spray/mists ; Eye contact .

#### Protective measures

Open windows to ensure natural ventilation.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep/Store only in original container. Protect against : Frost .

#### Hints on joint storage

Storage class (TRGS 510) : 10

### 7.3 Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

ETHANOL ; CAS No. : 64-17-5

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 200 ppm / 380 mg/m<sup>3</sup>  
Peak limitation : 4(II)  
Remark : Y  
Version : 23.06.2022

2-BUTOXYETHANOL ; CAS No. : 111-76-2

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 10 ppm / 49 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : H,Y  
Version : 23.06.2022

Limit value type (country of origin) : STEL ( EC )  
Limit value : 50 ppm / 246 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019

Limit value type (country of origin) : TWA ( EC )  
Limit value : 20 ppm / 98 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019

#### Biological limit values

2-BUTOXYETHANOL ; CAS No. : 111-76-2

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Butoxyacetic acid (after hydrolysis) / Urine (U) / End of exposure or end of shift ; At long term exposure: after several previous shifts  
Limit value : 150 mg/g Creatinine  
Version : 25.02.2022

#### DNEL-/PNEC-values

##### DNEL/DMEL

2-BUTOXYETHANOL ; CAS No. : 111-76-2

Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** C+P Der Reiniger für Stahlschränke  
**Revision date :** 10.02.2023  
**Print date :** 11.05.2023

**Version (Revision) :** 2.0.6 (2.0.5)

---

Limit value : 246 mg/m<sup>3</sup>  
ETHANOL ; CAS No. : 64-17-5  
Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 1900 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 950 mg/m<sup>3</sup>  
2-BUTOXYETHANOL ; CAS No. : 111-76-2  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 98 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 663 mg/m<sup>3</sup>  
ETHANOL ; CAS No. : 64-17-5  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 343 mg/kg  
2-BUTOXYETHANOL ; CAS No. : 111-76-2  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 75 mg/kg  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Short-term  
Limit value : 89 mg/kg  
**PNEC**  
ETHANOL ; CAS No. : 64-17-5  
Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 0,96 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,79 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Limit value : 3,6 mg/l  
Limit value type : PNEC (Sediment, marine water)  
Limit value : 2,9 mg/kg  
Limit value type : PNEC (Soil)  
Limit value : 0,63 mg/l  
Limit value type : PNEC (Secondary poisoning)  
Limit value : 0,72 mg/kg  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 580 mg/l  
2-BUTOXYETHANOL ; CAS No. : 111-76-2  
Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 8,8 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,88 mg/l  
Limit value type : PNEC (Sediment, freshwater)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : C+P Der Reiniger für Stahlschränke  
Revision date : 10.02.2023  
Print date : 11.05.2023

Version (Revision) : 2.0.6 (2.0.5)

Limit value : 34,6 mg/kg  
Limit value type : PNEC (Soil)  
Limit value : 2,33 mg/kg  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 463 mg/l

## 8.2 Exposure controls

### Personal protection equipment

#### Eye/face protection



Wear suitable safety goggles in case of splash.

**Suitable eye protection**  
EN 166.

#### Skin protection

##### Hand protection



**Suitable gloves type** : EN 374.  
**Suitable material** : NBR (Nitrile rubber)  
**Breakthrough time** : 480 min.  
**Thickness of the glove material** : 0.4 mm

**Remark** : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Respiratory protection



Respiratory protection necessary at: exceeding exposure limit values

##### Suitable respiratory protection apparatus

Combination filtering device  
Type : A

##### Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

#### General information

Do not put any product-impregnated cleaning rags into your trouser pockets. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. P362+P364 - Take off contaminated clothing and wash it before reuse. P264 - Wash hands thoroughly after handling.

## 8.3 Additional information

No tests have been performed. Selection made for preparations according to the best available knowledge and information on ingredients. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use.

## SECTION 9: Physical and chemical properties

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : C+P Der Reiniger für Stahlschränke  
Revision date : 10.02.2023  
Print date : 11.05.2023

Version (Revision) : 2.0.6 (2.0.5)

## 9.1 Information on basic physical and chemical properties

### Appearance

Physical state : Liquid

Colour : colourless

### Odour

characteristic

### Safety characteristics

Solidifying point :	( 1013 hPa )	-4,5	°C	
Initial boiling point and boiling range :	( 1013 hPa )	80	°C	
Flash point :		approx. 50	°C	DIN EN ISO 13736
Auto-ignition temperature :	( ETHANOL )	363	°C	Literature value
Flammability :		flammable		
Lower explosion limit :	( ETHANOL )	3,5	Vol-%	Literature value
Upper explosion limit :	( ETHANOL )	15	Vol-%	Literature value
Vapour pressure :	( 50 °C )	not relevant		
Density :	( 20 °C )	0,99	g/cm <sup>3</sup>	
Water solubility :	( 20 °C )	completely miscible		
pH :	( 20 °C )	11,4		
Flow time :	( 20 °C )	19	s	DIN-cup 4 mm
Cinematic viscosity :	( 20 °C )	<	30	mm <sup>2</sup> /s
Relative vapour density :	( 20 °C )	not determined		
Maximum VOC content (EC) :		11	Weight-%	
Maximum VOC content (Switzerland) :		11,5	Weight-%	
Taxable VOC content (Switzerland) :		11,5	Weight-%	

## 9.2 Other information

Not sustaining combustion. UN Test L.2: Sustained combustibility test

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non-reactive under normal use conditions.

### 10.2 Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3 Possibility of hazardous reactions

Do not spray on naked flames or any incandescent material.

### 10.4 Conditions to avoid

No information available.

### 10.5 Incompatible materials

No information available.

### 10.6 Hazardous decomposition products

No known hazardous decomposition products.  
Decomposition products in case of fire: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Acute oral toxicity

Parameter : ATEmix

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** C+P Der Reiniger für Stahlschränke  
**Revision date :** 10.02.2023  
**Print date :** 11.05.2023

**Version (Revision) :** 2.0.6 (2.0.5)

Exposure route : Oral  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( ETHANOL ; CAS No. : 64-17-5 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 10470 mg/kg  
Method : OECD 401  
Parameter : LD50 ( 2-BUTOXYETHANOL ; CAS No. : 111-76-2 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 1250 - 1490 mg/kg  
Method : OECD 401

**Acute dermal toxicity**

Parameter : ATEmix  
Exposure route : Dermal  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( 2-BUTOXYETHANOL ; CAS No. : 111-76-2 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 841 mg/kg  
Method : OECD 402  
Parameter : LD50 ( ETHANOL ; CAS No. : 64-17-5 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 20 g/kg

**Acute inhalation toxicity**

Parameter : ATEmix  
Exposure route : Inhalation  
Effective dose : > 20 mg/l  
Parameter : LC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 116,9 - 133,8 mg/l  
Exposure time : 4 h  
Method : OECD 403  
Parameter : LC50 ( 2-BUTOXYETHANOL ; CAS No. : 111-76-2 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 2 - 20 mg/l  
Exposure time : 4 h

**Corrosion**

**Skin corrosion/irritation**

No further relevant information available.

**Serious eye damage/eye irritation**

No further relevant information available.

**Respiratory or skin sensitisation**

**Skin sensitisation**

No further relevant information available.

**Sensitisation to the respiratory tract**

No further relevant information available.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

**Carcinogenicity**

No further relevant information available.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : C+P Der Reiniger für Stahlschränke  
Revision date : 10.02.2023  
Print date : 11.05.2023

Version (Revision) : 2.0.6 (2.0.5)

**Germ cell mutagenicity**

No further relevant information available.

**Reproductive toxicity**

No further relevant information available.

**STOT-single exposure**

No further relevant information available.

**STOT-repeated exposure**

No further relevant information available.

**Aspiration hazard**

No further relevant information available.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Toxicokinetics, metabolism and distribution**

None

**Other adverse effects**

May be absorbed through the skin. Has degreasing effect on the skin. Frequently or prolonged contact with skin may cause dermal irritation.

**Additional information**

Preparation not tested. The statement is derived from the properties of the single components.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity**

**Acute (short-term) fish toxicity**

Parameter :	LC50 ( ETHANOL ; CAS No. : 64-17-5 )
Species :	Pimephales promelas (fathead minnow)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	14,2 g/l
Exposure time :	96 h
Parameter :	LC50 ( 2-BUTOXYETHANOL ; CAS No. : 111-76-2 )
Species :	Oncorhynchus mykiss (Rainbow trout)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	1474 mg/l
Exposure time :	96 h
Method :	OECD 203

**Chronic (long-term) fish toxicity**

Parameter :	NOEC ( ETHANOL ; CAS No. : 64-17-5 )
Species :	Danio rerio (zebrafish)
Evaluation parameter :	Chronic (long-term) fish toxicity
Effective dose :	250 mg/l
Exposure time :	120 h
Method :	OECD 212
Parameter :	NOEC ( 2-BUTOXYETHANOL ; CAS No. : 111-76-2 )
Species :	Danio rerio (zebrafish)
Evaluation parameter :	Chronic (long-term) fish toxicity
Effective dose :	> 100 mg/l
Exposure time :	21 D
Method :	OECD 204



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : C+P Der Reiniger für Stahlschränke  
Revision date : 10.02.2023  
Print date : 11.05.2023

Version (Revision) : 2.0.6 (2.0.5)

## Acute (short-term) toxicity to crustacea

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Daphnia  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : 5012 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( 2-BUTOXYETHANOL ; CAS No. : 111-76-2 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : 1550 mg/l  
Exposure time : 48 h  
Method : DIN 38412 / part 11

## Chronic (long-term) toxicity to aquatic invertebrate

Parameter : NOEC ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Daphnia  
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate  
Effective dose : 9,6 mg/l  
Exposure time : 10 D  
Parameter : NOEC ( 2-BUTOXYETHANOL ; CAS No. : 111-76-2 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate  
Effective dose : 100 mg/l  
Exposure time : 21 D  
Method : OECD 211

## Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Chlorella vulgaris  
Evaluation parameter : Inhibition of growth rate  
Effective dose : 675 mg/l  
Exposure time : 4 D  
Method : OECD 201  
Parameter : EC50 ( 2-BUTOXYETHANOL ; CAS No. : 111-76-2 )  
Species : Pseudokirchneriella subcapitata  
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria  
Effective dose : 1840 mg/l  
Exposure time : 72 h  
Method : OECD 201

## Chronic (long-term) toxicity to aquatic algae and cyanobacteria

Parameter : NOEC ( 2-BUTOXYETHANOL ; CAS No. : 111-76-2 )  
Species : Pseudokirchneriella subcapitata  
Evaluation parameter : Chronic (long-term) toxicity to aquatic algae and cyanobacteria  
Effective dose : 286 mg/l  
Exposure time : 72 h  
Method : OECD 201

## Toxicity to microorganisms

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Bacteria toxicity  
Effective dose : 5,8 g/l  
Exposure time : 4 h

## 12.2 Persistence and degradability

According to the recipe, contains no AOX. The surfactant contained in this mixture complies with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

### Biodegradation

Parameter : Biodegradation ( ETHANOL ; CAS No. : 64-17-5 )

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : C+P Der Reiniger für Stahlschränke  
Revision date : 10.02.2023  
Print date : 11.05.2023

Version (Revision) : 2.0.6 (2.0.5)

Inoculum : Biodegradation  
Evaluation parameter : Aerobic  
Degradation rate : approx. 84 %  
Test duration : 20 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Parameter : Biodegradation ( 2-BUTOXYETHANOL ; CAS No. : 111-76-2 )  
Inoculum : Biodegradation  
Degradation rate : 88 %  
Test duration : 20 D

## 12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

## 12.4 Mobility in soil

No information available.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7 Other adverse effects

No information available.

## 12.8 Additional ecotoxicological information

After neutralisation, reduction in toxic effects is observed.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Directive 2008/98/EC (Waste Framework Directive)

##### Before intended use

##### Waste codes/waste designations according to EWC/AVV

07 06 01\* (Aqueous washing liquids and mother liquors)

20 01 29\* (Detergents containing hazardous substances)

##### Other disposal recommendations

Dispose of waste according to applicable legislation. Dispose of contents/container to an appropriate recycling or disposal facility. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

### 13.2 Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## SECTION 14: Transport information

### 14.1 UN number

No dangerous good in sense of these transport regulations.

### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

### 14.4 Packing group

No dangerous good in sense of these transport regulations.

### 14.5 Environmental hazards

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : C+P Der Reiniger für Stahlschränke  
Revision date : 10.02.2023  
Print date : 11.05.2023

Version (Revision) : 2.0.6 (2.0.5)

No dangerous good in sense of these transport regulations.

## 14.6 Special precautions for user

None

## 14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Authorisations and/or restrictions on use

##### Restrictions on use

Use restriction according to REACH annex XVII, no. : 40, 75

##### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

##### Other regulations (EU)

##### Labelling for contents according to regulation (EC) No. 648/2004

< 5 % non-ionic surfactants

#### National regulations

##### Störfallverordnung (12. BImSchV)

Category : P5b Flammable liquids

##### Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 5 %

Weight fraction (Number 5.2.4. III) : < 1 %

##### Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

### 15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

09. Information on basic physical and chemical properties · 11. Endocrine disrupting properties · 12. Endocrine disrupting properties

### 16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches Übereinkommen über die Beförderung gefährlicher Güter auf der Straße)

AOX: adsorbierbare organisch gebundene Halogene

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS: Chemical Abstracts Service (Unterabteilung der American Chemical Society)

CLP: Verordnung (EG) Nr. 1272/2008 über die Einstufung, Kennzeichnung und Verpackung von Stoffen und Gemischen (Classification Labelling and Packaging)

EAK / AVV: europäischer Abfallartenkatalog / Abfallverzeichnis-Verordnung

ECHA: Europäische Chemikalienagentur (European Chemicals Agency)

EINECS: : Altstoffverzeichnis (European Inventory of Existing Commercial Chemical Substances)

GHS: Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien (Globally Harmonized System of Classification and Labelling of Chemicals)

IATA: Internationale Luftverkehrs-Vereinigung (International Air Transport Association)

ICAO: Internationale Zivilluftfahrtorganisation (International Civil Aviation Organization)

IMDG: Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffverkehr (International Maritime Code for Dangerous Goods)

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** C+P Der Reiniger für Stahlschränke  
**Revision date :** 10.02.2023  
**Print date :** 11.05.2023

**Version (Revision) :** 2.0.6 (2.0.5)

---

RID: Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr (Règlement concernant le transport international ferroviaire de marchandises dangereuses)  
TRGS: Technische Regel für den Umgang mit Gefahrstoffen  
VbF: Verordnung über brennbare Flüssigkeiten  
VOC: flüchtige organische Verbindung (volatile organic compound)  
VVEA: Verordnung über die Vermeidung und die Entsorgung von Abfällen  
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe  
WGK: Wassergefährdungsklasse

**16.3 Key literature references and sources for data**

DGUV: GESTIS-Stoffdatenbank  
ECHA: Classification And Labelling Inventory  
ECHA: Pre-registered Substances  
ECHA: Registered Substances  
EC: Safety Data Sheet of Suppliers  
ESIS: European Chemical Substances Information System  
GDL: Gefahrstoffdatenbank der Länder  
UBA Rigoletto: Wassergefährdende Stoffe  
Regulation (EC) No. 1907/2006 of the European Parliament and of the Council  
Regulation (EC) No. 1272/2008 of the European Parliament and of the Council

**16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

**16.5 Relevant H- and EUH-phrases (Number and full text)**

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.

**16.6 Training advice**

None

**16.7 Additional information**

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---